

Arte

Arte is a top of the range specially formulated acrylic emulsion based latex coating pigmented system with the right properties to build various decorative patterns. Its good virtues include good washability, superior scrub resistance, smooth finish, color acceptance & retention property and a superior finish. Its unique formula is specially designed to match ambience of the interiors and decorations thereof.

- **Substrate:** Concrete, cement plaster, masonry and gypsum.
- **Area of Use:** Interior decorations.
- **Finish:** Rough and Matt.
- **Color:** Any color required.
- **Spread Rate:** Covers 6 to 8 m²/L.
- **Drying Time (30° C):** Set to touch: 1 – 2 hours.
Ready for Recoat: app 2 - 3 hours.

ارتيه

ارتيه من اصباغ الديكورات العلاية الجودة تمكنا من الحصول على اشكال رملية ناعمة متعددة . من محاسن اصباغ ارتيه انها صلبة قابلة للتنظيف , وهي ذات تركيبة خاصة تمنح الحوائط الداخلية رونقا "وجمالا" .

- أماكن الإستخدام : الأسطح الداخلية (الإسمنت , الطابوق , الجبس)
- الملمس : خشن ومطفي
- الألوان : حسب الطلب
- معدل التغطية : 6 - 8 (متر مربع / لتر)
- معدل الجفاف (30 درجة مئوية) : 1 - 2 ساعة
- لطبقة ثانية يجب الإنتظار 2 - 3 ساعة

**Stir well before usage.*

PW/1005 Primer Sealer	PW/2505 Stucco Putty	PW/3205 Platinum Emulsion	PW/3630 Arte
1 Coat	2 Coats	1 Coat	1 Coat

Before applying Arte, prepare well the wall by using EVI primer, EVI stucco putty and EVI emulsion top coat.



www.evivernici.com
U.A.E: P.O.Box: 18831, Dubai, UAE Email: info@evivernici.com
Tel: +971 4 251 22 08, Fax: +971 4 251 02 36, Toll Free Hotline in UAE: 800EVI
UAE-KSA-OMAN-QATAR-KUWAIT-IRAQ-LEBANON-CANADA-ITALY-NIGERIA



ISO 9001-2008, ISO 14001-2004, ISO 18001-2007



scan code for
EVI information



Arte

Wall's Masterpiece

