

Atmosfera

Atmosfera is a top of the range specially formulated acrylic emulsion based latex coating pigmented system with the right properties to build various decorative patterns. Its good virtues include good washability, superior scrub resistance, color acceptance and retention property, and a superior finish. Its unique formula is specially prepared to match ambiance of the interiors and decorations thereof.

- **Substrate:** Concrete, cement plaster, masonry and gypsum.
- **Area of Use:** Interior decorations.
- **Finish:** Rough and Matt.
- **Color:** White based to be mixed with the color tubes as per customer requirements.
- **Spread Rate:** Covers 6 - 8 m²/L.
- **Drying Time (30° C):** Set to touch: 1 - 2 hours.
Ready to recoat: app. 2 - 3 hours.

أتموسفيرا

من أصباغ الديكورات الأكريليكية العالية الجودة تمكنا من الحصول على أشكال وتصاميم متنوعة. من محاسن أصباغ أتموسفيرا أنها صلبة و قابلة للغسل ولها تركيبة خاصة تمنح الحوائط الداخلية رونقا وجمالا".

- أماكن الإستخدام : الأسطح الداخلية (الإسمنت , الطابوق , الجبس)
- الملمس : خشن و مطفي
- الألوان : الأبيض وكافة الألوان الأخرى حسب الطلب .
- معدل التغطية : 6 - 8 متر مربع / لتر
- معدل الجفاف (30 درجة مئوية) : 1 - 2 ساعة .
- لطبقة ثانية يجب الإنتظار من 2 - 3 ساعات .

**Stir well before usage.*

PW/1005 Primer Sealer	PW/2505 Stucco Putty	PW/3205 Platinum Emulsion	PW/3629 Atmosfera
1 Coat	2 Coats	1 Coat	1-2 Coats

Before applying Atmosfera, prepare well the wall by using EVI primer, EVI stucco putty and EVI emulsion top coat.



www.evivernici.com
U.A.E: P.O.Box: 18831, Dubai, UAE Email: info@evivernici.com
Tel: +971 4 251 22 08, Fax: +971 4 251 02 36, Toll Free Hotline in UAE: 800EVI

UAE • KSA • OMAN • QATAR • KUWAIT • IRAQ • LEBANON • CANADA • ITALY • NIGERIA

Intertek ISO 9001-2008, ISO 14001-2004, ISO 18001-2007



PAINTS & COATING SOLUTIONS

Atmosfera

Wall's Masterpiece



Scan code for
EVI information

