

Cocodrillo

Cocodrillo is a top of the line water based finish that has the Crocodile animal print finish. It creates a rough but appealing finish and can end up in different patterns utilizing the imagination of an artist and the skills of the applicator. The product can be over coated with patina or loro to give a pleasing look. The product is very hygienic and has a good anti fungal properties.

- **Substrate:** Concrete, plaster, masonry and gypsum.
- **Area of Use:** Interior with ability to overcoat if needed.
- **Finish:** Rough and plaster like.
- **Color:** As per the end user demand.
- **Spread Rate:** Covers 1 to 1.5 m²/L. (The coverage is not very significant as it can be applied to varying thickness.)
- **Drying Time (30° C):** Set to touch: 2 – 3 hours.
Ready for Recoat: at touch dry stage.

كوكو دريلو

من الأصباغ المائية العالية الجودة , كما أنها تمكن المستخدم من الحصول على أشكال وتصاميم خشنة متنوعة وذلك حسب طريقة التطبيق .

يمكن حماية المنتج بإضافة طبقة من باتيناتو أو لورينتو ... وذلك لإعطاء أشكال متنوعة .
من محاسن أصباغ كوكو دريلو أنها مواد مضادة للتلف وسهلة التطبيق .

- أماكن الإستخدام : الأسطح الداخلية (الإسمنت , الطابوق , الجبس)
- اللمس : خشن و نافر
- الألوان : حسب الطلب .
- معدل التغطية : 1 – 1.5 متر مربع / لتر حسب السماكة المطلوبة
- معدل الجفاف (30 درجة مئوية) : 2 – 3 ساعات .
- لطبقة ثانية يجب الإنتظار حين إنتهاء مرحلة جفاف الطبقة الأولى .

**Stir well before usage.*

PW/1051
All Weather
Tex Primer

PW/3902
Cocodrillo

PW/3627
Patina

1 Coat

2 Coats

As required

Apply EVI primer using a roller.
Wait till dry then follow the steps.

1

2



www.evivernici.com
U.A.E: P.O.Box: 18831, Dubai, UAE Email: info@evivernici.com
Tel: +971 4 251 22 08, Fax: +971 4 251 02 36, Toll Free Hotline in UAE: 800EVI
UAE - KSA - OMAN - QATAR - KUWAIT - IRAQ - LEBANON - CANADA - ITALY - NIGERIA



ISO 9001-2008, ISO 14001-2004, ISO 18001-2007



scan code for
EVI information



Cocodrillo

Wall's Masterpiece