

Loro

Loro is a top of the range specially formulated acrylic emulsion based latex coating pigmented system with the right properties to build various decorative patterns. Its good virtues include good washability, superior scrub resistance, smooth finish, color acceptance & retention property and a superior finish. Its unique formula is specially designed to match ambience of the interiors and decorations thereof.

- **Substrate:** Concrete, cement plaster, masonry and gypsum.
- **Area of Use:** Interior decorations.
- **Finish:** Smooth and Glossy.
- **Color:** Any golden color required.
- **Spread Rate:** Covers 8 to 10 m²/L.
- **Drying Time (30° C):** Set to touch: 1 – 2 hours.
Ready for Recoat: app 2 - 3 hours.


لورو من اصباغ الديكورات العلية الجودة تمكنا من الحصول على اشكال ذهبية لؤلؤية . من محاسن اصباغ لورو انها صلبة قابلة للتنظيف , وهي ذات تركيبة خاصة تمنح الحوائط الداخلية رونقا "وجمالا".

- أماكن الإستخدام : الأسطح الداخلية (الإسمنت , الطابوق , الجبس)
- الملمس : ناعم ذو لمعان ذهبي لؤلؤي
- الألوان : حسب الطلب
- معدل التغطية : 8 - 10 (مترمربع / لتر)
- معدل الجفاف (30 درجة مئوية) : 1 - 2 ساعة.
- لطبقة ثانية يجب الانتظار من 2 - 3 ساعات .

**Stir well before usage.*

PW/1005 Primer Sealer	PW/2505 Stucco Putty	PW/3205 Platinum Emulsion	PW/3623 Loro
1 Coat	2 Coats	1 Coat	2 Coats

Before applying Loro, prepare well the wall by using EVI primer, EVI stucco putty and EVI emulsion top coat.




U.A.E: P.O.Box: 18831, Dubai, UAE Email: info@evivernici.com
Tel: +971 4 251 22 08, Fax: +971 4 251 02 36, Toll Free Hotline in UAE: 800EVI

UAE - KSA - OMAN - QATAR - KUWAIT - IRAQ - LEBANON - CANADA - ITALY - NIGERIA



ISO 9001-2008, ISO 14001-2004, ISO 18001-2007



scan code for
EVI information



Loro

Wall's Masterpiece