

Rustico

Rustico is a top of the range specially formulated acrylic emulsion based latex coating pigmented system with the right properties to build various decorative patterns. Its good virtues include good washability, superior scrub resistance, colour acceptance, retention property and a superior finish. Its unique formula is specially prepared to match ambience of the interiors and decorations thereof. It has the effect of fine pearly sand.

- **Substrate:** Concrete, cement plaster, masonry and gypsum.
- **Area of Use:** Interior decorations.
- **Finish:** Rough Matt finish.
- **Color:** Any pearl color required.
- **Spread Rate:** Covers 8 m²/L.
- **Drying Time (30° C):** Set to touch: 1 – 2 hours.
Ready to recoat: app. 2 - 3 hours.

روستيكو

من أصباغ الديكورات الأكريليكية العالية الجودة تمكنا من الحصول على أشكال وتصاميم متنوعة . من محاسن أصباغ روستيكو أنها صلبة و قابلة للغسل ذات ملمس رملي ناعم ولؤلؤي ولها تركيبة خاصة تمنح الحوائط الداخلية رونقا "وجمالا".

- أماكن الإستخدام : الأسطح الداخلية (الإسمنت , الطابوق , الجبس)
- الملمس : رملي ناعم ولؤلؤي وطففي
- الألوان : الألوان اللؤلؤية المتوفرة في بطاقة الألوان .
- معدل التغطية : 8 متر مربع / لتر
- معدل الجفاف (30 درجة مئوية) : 1 – 2 ساعة .

**Stir well before usage.*

PW/1005 Primer Sealer	PW/2505 Stucco Putty	PW/3205 Platinum Emulsion	PW/3638 Rustico
1 Coat	2 Coats	1 Coat	2 Coats

Before applying Rustico prepare well the wall by using EVI primer, EVI stucco putty and EVI emulsion top coat.



U.A.E. P.O.Box: 18831, Dubai, UAE Email: info@evivernici.com
Tel: +971 4 251 22 08, Fax: +971 4 251 02 36, Toll Free Hotline in UAE: 800EVI
UAE • KSA • OMAN • QATAR • KUWAIT • IRAQ • LEBANON • CANADA • ITALY • NIGERIA



ISO 9001-2008, ISO 14001-2004, ISO 18001-2007



scan code for
EVI information



Rustico

Wall's Masterpiece