

ANTIQUÉ TOUCH

Product code: PS/3631

Composition and Application Field

EVI Antiqué Touch is a top of the line solvent based finish whose looks brings history to the present day era. It exhibits a finish very much akin to the historical concepts of the paintings and enhances the richness of the interiors of walls with a traditional look. It creates an appealing finish and can end up in different patterns utilizing the imagination of an artist and the skills of the applicator on practically any surface. The product can be over coated with good quality exterior emulsion colours to give a pleasing look. The product is very hygienic. The maintenance cost is low. The product has virtually long life and can withstands extreme conditions as it can be coated to good thickness.

Substrates: Concrete, plaster, masonry, gypsum.

Area of Use: Interior with ability to overcoat if needed

Specification

Finish	: Wall application and plaster, gypsum
Color	: Any color
Specific gravity	: 0.84 +/- 0.02
Solids (% by volume)	: 17 +/- 2%
Diluent	: Synthetic Thinner
Flash point	: 38°C
Spread Rate	: 5.5 sq.m ² /l at 30 microns

Drying Time (30° C)	: Set to touch: 2-3 hours. Ready for Recoat: at touch dry stage.
Recommended DFT	: App 30-40 microns

Surface Preparation

A good surface preparation and following the method statement / recommended system procedure of EVI is an ideal recommendation for the application EVI Antiqué Touch.

Exclusions for successful application include perpetually wet surfaces and also large cavities on wood, metal & concrete surfaces.

Ensure the surface is clean, dry & free from all loose or flaking particles.

Application Method

Adequate ventilation is an ideal situation as it helps in drying and the good application itself. Avoid high humid conditions i.e., >95% when condensation is likely to interfere and also when the surface temperature is at least 3°C above dew point. One can add minimum quantity of sweet water for getting the right consistency depending on the speed and skill of the applicator. One should

apply with a putty knife or a broad bladed knife and spread it evenly to the desired pattern. Allow to dry and then repeat the applications to the desired thickness. It is advisable to build up the quote with nominal thickness per application. This would ensure proper cure and capability of drying without cracks. If coloring is required use a natural colour of EVI Antiqué finish and apply a good layer of good quality external emulsion as per the desired colour.

Storage and Shelf Life

Under dry and cool condition, storage stability can be sound up to 18 months in original sealed containers.

Handling

Disposal: As per the guidance and legislations of the local Authority e.g., by controlled landfill. In case of doubt, consult local authority. Do not empty into drains, sewers or other water courses.

Safety Precaution

Avoid contact with the skin and eyes. Wear suitable protective clothing such as overalls, goggles, dust mask and gloves. Use a barrier cream. Ensure that there is adequate ventilation in the area where the product is being applied. Do not breathe vapour or spray. MSDS is available on request for the safe handling of this product.

First Aid

Eyes: In the event of accidental splashes, flush eyes with warm water immediately and obtain medical advice.

Skin: Wash skin thoroughly with soap and water or approved industrial cleaner. Do not use solvent or thinners.

Inhalation: Remove to fresh air, loosen collar and keep patient rested.

Ingestion: In case of accident ingestion DO NOT INDUCE VOMITING. Obtain immediate medication attention.