



## **Technical Data Sheet**

# 2K WHITE GLOSS (AUTO) HARDENER

Product code: PS3866H

#### **Description & Suggested Use**

The product is a HARDENER. Suggested use: Chemical cure of Acrylic 2K Topcoat White Glossy (Auto).

**General Information** 

The Acrylic 2K Topcoat White Glossy (Auto) mixed with the hardener PS3866H shows medium pot life and speed of cure. After drying, the catalyst allows the Acrylic to obtain a hard film with good clarity and fair light fastness. Anyway, the catalyst does not prevent the Acrylic from yellowing upon ageing.

#### **Specification**

Specific Gravity @  $20^{\circ}$ C (kg/L) :  $0.93 \pm 0.01$ Solid Content (% by volume) :  $24 \pm 1$ NCO (%) :  $4 \pm 1$ 

### Storage & Shelf Life

Keep the cans tightly close in a well ventilated place. Temperature should be controlled and kept between 10 to 30°C. The product is moisture sensitive and reacts with atmospheric humidity, protect from moisture contamination.

Product can be kept up to 18 months from production date only if storing instructions are correctly followed.

#### **Safety Precaution**

Avoid contact with the skin and eyes. Wear suitable protective clothing such as overalls, goggles, dust mask and gloves. Use a barrier cream. Other industrial practices are applicable. Ensure that there is adequate ventilation in the area where the product is being applied. Do not breathe vapour or spray.

MSDS is available on request for the safe handling of this product.

#### **FIRST AID**

Eyes: In the event of accidental splashes, flush eyes with warm water immediately and obtain medical advice. Skin: Wash skin thoroughly with soap and water or approved Industrial cleaner. DO NOT USE solvent or thinners.

Inhalation: Remove to fresh air, loosen collar and keep patient rested.

Ingestion: In case of accidental ingestion DO NOT INDUCE VOMITING. Obtain immediate medical attention.